

529, 632

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 April 2004 (15.04.2004)


PCT

(10) International Publication Number
WO 2004/031676 A1

- (51) International Patent Classification⁷: **F28F 1/02**
- (21) International Application Number:
PCT/JP2003/012616
- (22) International Filing Date: 1 October 2003 (01.10.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2002-290180 2 October 2002 (02.10.2002) JP
60/421,082 25 October 2002 (25.10.2002) US
2003-327179 19 September 2003 (19.09.2003) JP
- (71) Applicant (for all designated States except US): **SHOWA DENKO K.K.** [JP/JP]; 13-9, Shiba Daimon 1-chome, Minato-ku, Tokyo 105-8518 (JP).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **TAKE, Koichiro** [JP/JP]; c/o Oyama Regional Office, Showa Denko K. K., 480, Inuzuka 1-chome, Oyama-shi, Tochigi 323-0811 (JP).
- (74) Agents: **SHIMIZU, Hisayoshi** et al.; Idemitsu Nagahori Building, 4-26, Minamisemba 3-chome, Chuo-ku, Osaka-shi, Osaka 542-0081 (JP).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: **HEAT EXCHANGING TUBE AND HEAT EXCHANGER**



(57) **Abstract:** A heat exchanging tube is provided with a flat tube main body having a predetermined length and a plurality of refrigerant passages extending in a tube longitudinal direction and arranged in a tube widthwise direction. The following relational equations (a) to (c) are satisfied: $W = 6 \text{ to } 18 \text{ mm}$... (a); $A_c/A_t \times 100 = 50 \text{ to } 70\%$... (b) and $P/L \times 100 = 350 \text{ to } 450\%$... (c), where "W" is a width of the tube main body, "Ac" is a total cross-sectional area of the refrigerant passages, "At" is a total cross-sectional area of the tube main body (including the refrigerant passages), "L" is an external perimeter of the tube main body and "P" is a total inner perimeter of the refrigerant passages. With this tube, enough pressure strength can be obtained and the passage resistance can be decreased while keeping the light weight, and further the heat exchanging performance can be improved.

WO 2004/031676 A1